

12-LEAD resting electrocardiograph

MORTARA'S NEXT
GENERATION
12-LEAD RESTING
ELECTROCARDIOGRAPH



ELI 210

PRODUCT FEATURES

- **Backlit LCD Display** – High-resolution display provides real time preview of 12-lead ECG and post-acquisition review of acquired ECG.
- **Mortara VERITAS Analysis Algorithm** – Internationally recognized Mortara resting interpretation algorithm provides silent second opinion for 12-lead ECG interpretation.
- **Full-size, Z-fold Paper** – Full-size paper (8.5" x 11" or A4 supported) output includes multiple Standard or Cabrera print options including 3+1, 3+3, 6-channel and 12-channel outputs.

E L I 2 1 0™ E L E C T R O C A R D I O G R A P H

Feature	Specifications
Instrument Type	12-lead Electrocardiograph
Input Channels	Simultaneous acquisition of 12 leads
Standard Leads Acquired	I, II, III, aVR, aVL, aVF, V1, V2, V3, V4, V5, V6
Waveform Display	Backlit, 1/4 VGA LCD 3-channel lead groups or complete 8-channel presentation
Input Impedance Input Dynamic Range Electrode Offset Tolerance Common Mode Rejection	Meet or exceed the requirements of ANSI/AAMI EC11
Patient Leakage Current Chassis Leakage Current	Meet or exceed requirements of ANSI/AAMI ES1
Digital Sampling Rate	10,000 s/sec/channel used for pacemaker spike detection; 1000 s/sec/channel used for recording and analysis
Special Functions	Optional Mortara VERITAS resting interpretation algorithm
Paper Type	Full size (8.5" x 11" or A4), Z-fold thermal paper; 250 sheets stored in paper tray
Thermal Recorder	Computer-controlled dot array; 8 dots/mm
Thermal Writer Speeds	5, 10, 25, or 50 mm/s
Gain Settings	5, 10, or 20 mm/mV
Report Print Formats	Standard or Cabrera: 3+1, 3+3 channel, 6-channel, 12-channel
Rhythm Print Formats	3-channel or 6-channel with configurable lead groups, or 12-channel
Keyboard Type	Elastomer keypad with soft-key menu and dedicated function keys
Frequency Response	0.05 to 300 Hz
Filters	High performance baseline filter; AC interference filter 50/60 Hz; low pass filters 40 Hz or 150 Hz
A/D Conversion	20 bit (1.17 microvolt LSB)
Device Classification	Class I, Type CF defibrillation proof applied parts
Weight	11.25 lb. (5.1kg) including battery
Dimensions	15.5" x 17" x 4" (39.4 cm x 43.2 cm x 10.2 cm)
Power Requirements	Universal AC power supply (100-240 VAC at 50/60 Hz) 50 VA. Internally rechargeable battery

*Specifications subject to change without notice.

S T A N D A R D A C C E S S O R I E S

- Patient Cable
- Accessory Starter Kit
- Operator's Manual
- Hospital Grade Power Cord

Warranty and Service

Mortara Instrument is committed to the highest level of customer support. Please contact us for the program which will be best suited for your needs.

Mortara Instrument, Inc.
7865 North 86th Street
Milwaukee, WI 53224
Tel: 414.354.1600
Tel: 800.231.7437
Service: 888.MORTARA
Fax: 414.354.4760

Mortara Rangoni Europe, Srl
(European Headquarters, Italy)
Via Oradour 7
40016 S. Giorgio di Piano, BO
Tel: +39.051.6654311
Fax: +39.051.6651012

Mortara Instrument GmbH
(Germany)
Kaninenberghöhe 50
45136 Essen
Tel: +49.201.268311
Fax: +49.201.268313

Mortara Instrument B.V.
(The Netherlands)
H. Dunantplein 6
3731 CL De Bilt
Postbus 131
3720 AC Bilthoven
Tel: +31.30.2205050
Fax: +31.30.2201531

 **Mortara INSTRUMENT**
The World Leader in ECG Technology

<http://www.mortara.com>
ISO 13485 Certified